### TECHNICAL SPECIFICATIONS

|                    | PARAMETERS                | MEASUREMENTS             |
|--------------------|---------------------------|--------------------------|
| BODY DIMENSIONS    | Length                    | 1955 mm                  |
|                    | Width                     | 754 mm                   |
|                    | Height                    | 1050 mm                  |
|                    | Wheel Base                | 1245 mm                  |
|                    | Ground Clearance          | 168 mm                   |
|                    | Kerb Weight               | 99 kg                    |
|                    | Seat Length               | 677 mm                   |
|                    | Seat Height               | 786 mm                   |
|                    | Fuel Tank Capacity        | 9 L                      |
| ENGINE             | Туре                      | 4 Stroke, SI Engine      |
|                    | Displacement              | 98.98 cc                 |
|                    | Max Engine Output         | 5.43 kW @ 7500 rpm       |
|                    | Max Torque                | 8.05 N-m @ 5000 rpm      |
|                    | Fuel System               | PGM- FI                  |
|                    | Bore X Stroke (mm)        | 47.000 X 57.049          |
|                    | Compression Ratio         | 10.0: 1                  |
|                    | Starting Method           | Self/Kick                |
|                    | Clutch Type               | Multiplate Wet Clutch    |
|                    | No. of Gears              | 4                        |
| TYRES & BRAKES     | Tyre Size & Type (Front)  | 2.75 - 17 41P, Tube Type |
|                    | Tyre Size & Type (Rear)   | 3.00 - 17 50P, Tube Type |
|                    | Brake Type & Size (Front) | Drum Type , 130mm        |
|                    | Brake Type & Size (Rear)  | Drum Type , 110mm        |
| FRAME & SUSPENSION | Frame Type                | Diamond Type             |
|                    | Front Suspension          | Telescopic               |
|                    | Rear Suspension           | Twin                     |
| ELECTRICALS        | Battery                   | 12V, 3.0Ah               |
|                    | Head Lamp                 | Bulb Type                |

Dealer Stamp





**Black With Red** 

**Black With Blue** 





**Black With Green** 

**Black With Gold** 



**Black With Grey** 



Honda Motorcycle & Scooter India Pvt. Ltd., Registered Office: Plot No. 1, Sector - 03, IMT Manesar, Distt. Gurugram, (Haryana) - 122050,

• Product shown in the picture may vary from actual product available in the market. • Accessories shown in the picture are not part of standard equipment. India; Website: www.honda2wheelersindia.com; Customer Care: customercare@honda2wheelersindia.com





## IMPRESSIVE MILEA GE PGM-FI

eSP Technology



Reduces friction and improves performance and fuel efficiency.

PENA-F

THE PROPERTY OF THE PROPERTY OF

Shine

PGM-FI system gives consistent power and more mileage.





The Combi-Brake System with Equalizer reduces braking distance, so you can ride with confidence.

Superior Suspension makes driving easy on all kinds of roads.



Longer, comfortable seat and great Ergonomics make even long journeys comfortable.



Easy ground touch and optimum seat height enhances your comfort.

# SUPERIS STILL Stylish Alloy Wheels



Adds to your style significantly.



Beautiful tank and side graphics increase your shine.



Shine



Magnificent aerodynamic front cowl and attractive headlamp.



# EFFECTIVE Shine

## Side Stand Engine Cut Off



Adding to the safety of the rider, it cuts off the ignition if the vehicle is put in gear when the side stand

### Light Weight Durable Diamond Frame



Light frame reduces the overall weight of the motorcycle which makes it easier to handle it. Durable & tough frame suited for variable road conditions and extremely convenient for carrying load.

## Small Turning Radius



Effective in tight corners & narrow roads.

### Strong Grab Rail



Makes the motorcycle elegant and practical.